

STYLE 42P

Style 42P is combination packing made from lubricated PTFE yarn with the corners of the packing reinforced with lubricated polyamide fibers.

Service

Style 42P is specifically designed for rotary and reciprocating application, sealing against water, sewage, oil, alkalis, acids, solvents, chemicals and food.

PROPERTY	
pH range	2 to 12
Temperature range	-85 DEG.C to +260 DEG.C
Pressure range	14 Mpa (maximum)
Shaft Speed	12 m/s (maximum)

Availability

The following square section material is available in coils
mm 3.0, 4.0, 5.0, 6.5, 8.0, 9.5, 12.0, 14.0, 16.0, 19.0, 22.0, 25.0

Head Office: 15/B, Vinod Apartments, Krantiveer Vasant Rao Naik X Lane, Gowalia Tank. Mumbai – 400036 INDIA

Tel.: 91 - 22 - 2389 0904 / 05 **Fax:** 91 - 22 - 2389 0907 **Email:** starflex@starflex.net

visit us at: www.starflex.net

Disclaimer: The datasheet relates to the material as supplied. The information contained herein is given in good faith, but no liability will be accepted by the company in relation to same. The acquisition of additional data may necessitate revision to parts, or all, of this data sheet, and such information will be supplied as it becomes available.

The information given and, in particular, any parameters, should be used for guidance purposes only. The company does not give any warranty that the product will be suitable for the use intended by the customer.